


Model #8287

Technical Data Sheet



be up to 28 sq. ft. (2.6 m2), as long as either H or W dimension is less than 84" [2134]. Mirrors larger than 28 sq. ft. (2.6 m2) or with either linear H or W dimension larger than 84" [2134] shall be supplied as multiple pieces. Made of 1/4" [6] polished plate glass.

Key Features & Specifications

- Clean lines of the framless mirror complements every bathroom
- Plate Glass 1/4" [6] thick Polished / other glazing options not available with polished edges
- Surface Mounted
- Polished edge available (only on "A" Glazing Mirrors)
- Various Sizes

American Specialties, Inc. 441 Saw Mill River Road, Yonkers, NY 10701 (914) 476-9000 | www.americanspecialties.com **Revision: R2** Issued: 11/1/2021 Revised: 5/2/2023

Model:#8287

American Specialties, Inc.

Model: #8287

Model #8287

Technical Data Sheet

Dura in 4	
Property	Value
Dimensions	Various Sizes Available
Construction	Plate Glass - 1/4" [6] thick - Polished
Mounting	Surface Mounted
Materials	<u>Glass:</u> Standard glazing is #1 quality, 1/4" [6.4] thick plate/float, silver coated and hermetically sealed with a uniform coating of electrolytic copper plating, warranted against silver spoilage for 15 years. Mirrors meet Federal Spec. DD-M 411C, ASTM C-1503, and ASTM C-1036-91.
Installatio	N
Surface mount ABA Standards	unit to wall using hardware supplied by installer. For compliance with 2010 ADA Accessibility Standards and 2015 install unit with bottom edge of reflecting surface no higher than 40" [1016] maximum Above Finished Floor.
Size Optio	NS STATES S
Plate Glass	8287-1620 – 16" [406] wide x 20" [508] high 8287-1624 – 16" [406] wide x 24" [610] high 8287-1824 – 18" [457] wide x 24" [610] high 8287-1830 – 18" [457] wide x 30" [762] high 8287-1836 – 18" [457] wide x 36" [914] high 8287-2430 – 24" [610] wide x 30" [762] high 8287-2436 – 24" [610] wide x 36" [914] high 8287-4824 – 48" [1219] wide x 24" [610] high
meet Federal S (B) Tempered G copper plating. DD-G1403B, Am	1/4" [6.4] #1 quality polished, silver coated and hermetically sealed with an electrolytic copper plating. Mirror bec. No. DD-M-411C, ASTM C-1503 and ASTM-C-1036-91. Image quality: Excellent lass - 1/4" [6.4] thick polished tempered glass with two coats of silver. Hermetically sealed with an electrolyti Back of mirror is finished and protected with a heavy waterproof paint. Glazing meets Federal Specification No endment 1, ASTM C-1503 and ASTM-C-1048-92. Image quality: Good
(A) Plate Glass meet Federal S (B) Tempered G copper plating. DD-G1403B, Am (C) Metal Mirro (D) Lexan Dura prevent scratch (E) Plexiglas [®] - (L) Mirror is fab glass with back protected with	1/4" [6.4] #1 quality polished, silver coated and hermetically sealed with an electrolytic copper plating. Mirror bec. No. DD-M-411C, ASTM C-1503 and ASTM-C-1036-91. Image quality: Excellent lass - 1/4" [6.4] thick polished tempered glass with two coats of silver. Hermetically sealed with an electrolyti Back of mirror is finished and protected with a heavy waterproof paint. Glazing meets Federal Specification No
A) Plate Glass meet Federal S B) Tempered G copper plating. DD-G1403B, Am C) Metal Mirro D) Lexan Dura prevent scratch E) Plexiglas [®] - L) Mirror is fab glass with back	1/4" [6.4] #1 quality polished, silver coated and hermetically sealed with an electrolytic copper plating. Mirror bec. No. DD-M-411C, ASTM C-1503 and ASTM-C-1036-91. Image quality: Excellent lass - 1/4" [6.4] thick polished tempered glass with two coats of silver. Hermetically sealed with an electrolyti Back of mirror is finished and protected with a heavy waterproof paint. Glazing meets Federal Specification No endment 1, ASTM C-1503 and ASTM-C-1048-92. Image quality: Good is -Type 304 alloy 18-8 stainless steel, 20 gauge polished to a #8 mirror finish. Image quality: Good Mirror - 1/4" [6.4] impact resistant polycarbonate sheet. Mirror face is provided with removable masking t ng during installation. Image quality: Very Good /4" [6.4] thick acrylic plastic, lightweight and highly shock resistant. Image quality: Very Good ricated with a 1/32" [0.8] thick vinyl interlayer bonded between two 1/8" [3] sheets of #1 quality polished plat silver. Hermetically sealed with a uniform coating of electrolytic copper plating. Back of mirror is finished an a heavy-duty waterproof paint. Laminated glass meets the performance criteria of Federal Spec. No. DD-M-45

CSI: 10 28 13 Toilet Accessories Page: 2 of 2

Revision: R2 Issued: 11/1/2021

Revised: 5/2/2023

Manufacturer reserves the right to make changes to the design, dimensions or functionality of the product without formal notice.